



1. TOUCH PANEL PIN ASSIGNMENT

1	Up	Glass Terminal
2	Right	Film Terminal
3	Down	Glass Terminal
4	Left	Film Terminal

2. MATERIAL CHARACTERISTICS

Property	Requirement
Surface treatment	Anti-glare
Haze	8%
Bottom glass thickness	1.1mm
Light transmission	80%
Operation temperature	-5~60 °C
Storage temperature	-30~70 °C
Operating Humidity	20~90%RH
Storage Humidity	20~90%RH
Surface hardness	3H (Min.)

3. ELECTRICAL CHARACTERISTICS

Property	Requirement
Type	Analog resistive 4 wire
Linearity	Max. 1.5%
X(2,4) resistance	400~900Ω
Y(1,3) resistance	200~500Ω
Insulation resistance	Min. 10MΩ (DC 25V)

- 4.A.A.:ACTIVE AREA
- 5.V.A.:VIEW AREA
- 6.D.O.:DIMENSIONAL OUTLINE
- 7.Tolerance no specified: ±0.5mm

MODEL	GP-057F-4S-01	TYPE	Analog Resistive	DATE	2006.06.27
UNIT	mm.	NO		CUSTOMER	
DRAWING	Daniel	NOTE	Four-Wire	APPROVED	

